

M23圆形信号连接器

现场接线

6孔

3+PE+4孔

3+PE+5孔

插孔
•直出线



插孔
•90°



1	型号	No.	M23-6FS.P-DL	M23-8FS.P-DL	M23-9FS.P-DL	M23-6FS.P-DL	M23-8FS.P-DL	M23-9FS.P-DL													
	极数		6p(6xφ2)	8p(4xφ2+4xφ1)	9p(4xφ2+5xφ1)	6p(6xφ2)	8p(4xφ2+4xφ1)	9p(4xφ2+5xφ1)													
	电缆出线直径		7-17mm	7-17mm	7-17mm	7-17mm	7-17mm	7-17mm													
	针脚排序																				
2	技术参数																				
	额定电压		630 V AC/DC		630 V (AC/DC) / 250 V (AC/DC)		630 V (AC/DC) / 250 V (AC/DC)														
	额定电流		28A		28A/8A		28A/8A														
	防护等级		IP67-插孔插针配合拧紧		IP67-插孔插针配合拧紧		IP67-插孔插针配合拧紧														
	温度范围		-20...+130°C		-20...+130°C		-20...+130°C														
	测试电压(两插针之间)		4000V		4000V/2500V		4000V/2500V														
	外壳材料		锌合金压铸件 黄铜, 镀镍		锌合金压铸件 黄铜, 镀镍		锌合金压铸件 黄铜, 镀镍														
	绝缘内嵌体材料		PA66/PBT,UL 94/V0		PA66/PBT,UL 94/V0		PA66/PBT,UL 94/V0														
	接触件 (插针/插孔)				<table border="1"> <thead> <tr> <th>类型</th> <th>压线范围</th> <th>订货号</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插孔 ∅ 1 mm</td> <td>0.14-0.5mm²</td> <td>EDF1-0.5</td> </tr> <tr> <td>0.5-1.0mm²</td> <td>EDF1-1.0</td> </tr> <tr> <td rowspan="2">插孔 ∅ 2 mm</td> <td>1.0-2.5mm²</td> <td>EDF2-2.5</td> </tr> <tr> <td>2.5-4.0mm²</td> <td>EDF2-4.0</td> </tr> </tbody> </table>		类型	压线范围	订货号	插孔 ∅ 1 mm	0.14-0.5mm ²	EDF1-0.5	0.5-1.0mm ²	EDF1-1.0	插孔 ∅ 2 mm	1.0-2.5mm ²	EDF2-2.5	2.5-4.0mm ²	EDF2-4.0		
类型	压线范围	订货号																			
插孔 ∅ 1 mm	0.14-0.5mm ²	EDF1-0.5																			
	0.5-1.0mm ²	EDF1-1.0																			
插孔 ∅ 2 mm	1.0-2.5mm ²	EDF2-2.5																			
	2.5-4.0mm ²	EDF2-4.0																			
	订货号																				
	订货范例		<div style="display: flex; justify-content: space-around; align-items: center;"> </div>																		
			1	连接器类型	2	电缆线号	3	电缆长度													
			订货型号的第二部分和第三部分可根据线号和长度不同自行修改, 电缆长度单位: M (米)																		