

M40 圆形电源连接器

现场接线

3+PE+2孔

3+PE+4孔

插孔

•直出线



插孔

•直出线



1		型号	No.	M40-6FS.P-DL	M40-8FS.P-DL															
极数		6p(4xφ3.6+2xφ2)			8p(4xφ3.6+4xφ2)															
电缆出线直径		13-28mm			13-28mm															
针脚排序																				
2		技术参数																		
额定电压		630V (AC/DC) / 250V (AC/DC)																		
额定电流		55A/28A																		
防护等级		IP67-插孔插针配合拧紧																		
温度范围		-20...+130°C																		
测试电压(两插针之间)		4000V/2500V																		
外壳材料		锌合金压铸件 黄铜, 镀镍																		
绝缘内嵌体材料		PA66/PBT, UL 94/V0																		
接触件 (插针/插孔)		<div style="display: flex; align-items: center;">  <table border="1" style="margin-left: 20px;"> <thead> <tr> <th>类型</th> <th>压线范围</th> <th>订货号</th> </tr> </thead> <tbody> <tr> <td rowspan="2">插孔 ∅ 2 mm</td> <td>1.0-2.5mm²</td> <td>EDF2-2.5</td> </tr> <tr> <td>2.5-4.0mm²</td> <td>EDF2-4.0</td> </tr> <tr> <td rowspan="3">插孔 ∅ 3.6mm</td> <td>1.5-4.0mm²</td> <td>EDF36-4.0</td> </tr> <tr> <td>4.0-6.0mm²</td> <td>EDF36-6.0</td> </tr> <tr> <td>6.0-10.0mm²</td> <td>EDF36-10.0</td> </tr> </tbody> </table> </div>				类型	压线范围	订货号	插孔 ∅ 2 mm	1.0-2.5mm ²	EDF2-2.5	2.5-4.0mm ²	EDF2-4.0	插孔 ∅ 3.6mm	1.5-4.0mm ²	EDF36-4.0	4.0-6.0mm ²	EDF36-6.0	6.0-10.0mm ²	EDF36-10.0
类型	压线范围	订货号																		
插孔 ∅ 2 mm	1.0-2.5mm ²	EDF2-2.5																		
	2.5-4.0mm ²	EDF2-4.0																		
插孔 ∅ 3.6mm	1.5-4.0mm ²	EDF36-4.0																		
	4.0-6.0mm ²	EDF36-6.0																		
	6.0-10.0mm ²	EDF36-10.0																		
订货号		IP67-插孔插针配合拧紧																		
订货范例		<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; width: 150px; height: 20px; background-color: #ccc;"></div> <div style="border: 1px solid black; width: 150px; height: 20px; background-color: #ccc;"></div> <div style="border: 1px solid black; width: 150px; height: 20px; background-color: #ccc;"></div> </div>																		
		1	2	3																
		连接器类型	电缆线号	电缆长度																
		订货型号的第二部分和第三部分可根据线号和长度不同自行修改, 电缆长度单位: M (米)																		